

TYPE:

ORDERING CODE:

APPROVAL:

JOB:

EFO-AAL-2R

DATE:

SPECIFICATIONS

Max Overall Dimensions: 12.44" (L) x 7.32" (W) x 4.63" (H) (316mm x 186mm x 118mm)

Trim / Flange Dimensions: 12.44" (L) x 7.32" (W) x 0.13" (H) (316mm x 186mm x 3mm)

Aperture Diameter: 2.0" (OD) (51mm) per lens

Rough-in / Cut out: 10.63" x 5.5" (270mm x 140mm)

Recess: 14.0" (356mm) to allow for fiber bend

Primary Material: Steel, Aluminum

Lens Type: Beveled glass, MBF-SOL softening lens available

Beam Angle: 15°, 25°, 40° or 60° *

*60° beam is achieved with no lens installed

Must request at time of order

Fiber Type: Large Core EFOFJ

Rotation: 360°

Max Tilt Angle: +/- 31°

Finishes: Black, White

Ferrule Requirement: Large Core bayonet, attached to Fibertail

Mounting: Fixtures mount to T-Bar ceiling grid with Erico 512HD Caddy Rails, Fiberstars

EFO-CR rails or others.

Order part EFO-AAL-2R-HC for hard ceiling mount

