


EFO Fiber Optic Fiber

End-Emitting



EFO OptiCore

For use with EFO-1+1 and EFO-AG illuminators. Consult factory for custom lengths sold by the foot. Factory FiberJacks assemblies or harnesses are strongly recommended, see above. Minimum bend radius is 8x inner diameter.



Printer-Friendly Spec Sheet

EFO-9/8mm

Outer Diameter: 0.35" (9 mm)

Inner Diameter : 0.27" (7 mm)

Outer Jacket Material: Black PVC

Minimum Bend Radius: 2.8" (72 mm)

Technical Remarks:



Printer-Friendly Spec Sheet

EFO-12/10mm


Outer Diameter: 0.47" (12 mm)

Inner Diameter : 0.39" (10 mm)

Outer Jacket Material: Black PVC

Minimum Bend Radius: 3.8" (96 mm)

Technical Remarks:



Printer-Friendly Spec Sheet

EFO-14/12mm

Outer Diameter: 0.55" (14 mm)

Inner Diameter : 0.47" (12 mm)


Outer Jacket Material: Black PVC

Minimum Bend Radius: 4.4" (112 mm)

Technical Remarks:



EFO-17/15mm



EFO-17/15mm

Outer Diameter: 0.67" (17 mm)

Inner Diameter : 0.59" (15 mm)


Outer Jacket Material: Black PVC

Material:

Minimum Bend Radius: 5.4" (136 mm)

Radius:

Printer-Friendly Spec Sheet Technical Remarks:



EFO-22/19mm

Outer Diameter: 0.87" (22 mm)

Inner Diameter : 0.75" (19 mm)

Outer Jacket Material: Black PVC

Material:

Minimum Bend Radius: 6.9" (176 mm)

Radius:

Printer-Friendly Spec Sheet Technical Remarks: