

LIGHTLY EXPRESSED® LIGHT BARS

description_ordering guide_specifications



light bars



TRIAxis

Description:

Similar to LightBeam, asymmetrical distribution. The unique design of this light bar has 3 different angles of distribution, 15°, 30° and 35°. This allows a broader wash of light into a display case or similar application.

Case Lighting Recommendations:

- (22) recommended for 24" cases
- (34) recommended for 36" cases
- (46) recommended for 48" cases
- (58) recommended for 60" cases
- (70) recommended for 72" cases

TRX				
ordering guide	Lit Length: () SPECIFY INCHES	Tail Length: () SPECIFY FEET	Finishes: S STANDARD CLEAR ANODIZED	Tail Exit: L LEFT R RIGHT C CUSTOM

Specifications: Beam Spread: 80° (ASYMMETRIC) Max Lit Lengths: 120" (3.56M) Base Sizes: 1.4" x 1.3" (35.56MM x 33MM) Mounting: LB-MB OR SIMILAR SURFACE MOUNT Technical Remarks: INTENDED FOR CASE AND CABINET LIGHTING BUT USEFUL WHEREVER A WIDE-DISPERSION, ASYMMETRICAL WASH IS REQUIRED. Cable Diameters: STANDARD SIZE: 7/8" MAX Max Fiber Capacity: 300 FIBERS Max Lamp Wattage: 150W METAL HALIDE
--

Isometric Key: L LENGTH UP TO 120" T TAIL LENGTH E TAIL EXIT, RIGHT OR LEFT	Isometric: THIS IS THE TOP RIGHT CORNER, USED WHEN DETERMINING THE TAILEXIT (LEFT TAIL EXIT SHOWN)	Cross Section:
--	--	---------------------------